

# Product Technical Data Sheet MANUFACTURER: AG Termopasty Grzegorz Gąsowski ul. Kolejowa 33 E. 18-218 Sokoły, phone 86 274 13 42

ul. Kolejowa 33 E, 18-218 Sokoły, phone 86 274 13 42

# **PVB Solvent**

High quality pure chemical agent. Designed for diluting the PVB 60 varnish. May be used to clean brushes, soiled equipment and elements due to painting or as a varnish remover. In order to obtain a thinner layer of PVB varnish, it is recommended to use the PVB solvent. It does not affect the colouration and does not tarnish the diluted product.

## **Application:**

- varnish remover,
- cleaning of brushes, soiled tools,
- It washes away the residues after soldering, including rosin.

# Physicochemical properties:

Parameters	UoM	Result
Relative density 20°C	g/cm³	~0,78-0,79
Viscosity	MPa·s	420

#### Packagings:

Volume	Type of packaging	Collective packaging	Item Code
500ml	plastic bootle	1	ART.AGT-239

### Warehousing:

Keep away from sources of heat, hot surfaces, sparks, open flames and other sources of ignition. Do not smoke. Use only outdoors or in a well-ventilated area.

Data contained in this document are consistent with the current state of our knowledge. They describe typical product properties and applications. However, it is up to the user to examine the suitability of this product for specific applications. We deny liability for the obtained results on the grounds that application conditions lie beyond our control.

